CROOKES

32060040
CRO133 25H840 PY PS3 BRS
Tubular light fitting

Description

- CROOKES 133 tubular light fitting
- End-caps ½ ring press-formed
- Optical diffuser
- Ø135 mm borosilicate-glass diffuser
- Single-piece housing with high mechanical and reinforced seal
- White powder-coated mounting plate
- Passive heat sink in aluminium
- Moulded EPDM gaskets



Light specifications and controlling

- High efficiency replaceable LED modules (IRC>80, 70 000 hours L80/B10@Tmax)
- Luminous flux: 9250 lm
- Colour temperature: 4000K
- Light mixing chamber
- Non-dimmable LED driver



Installation and maintenance

- Diameter: 133 mm
- Total length: 1587 mm
- 1 3x1,5mm² disconnectable plug lockable with threaded ring (capacity: Ø8 to 11 mm)
- Connection with disconnectable plug 3x1,5mm²
- 2 reinforced fixing straps in stainless steel with variable centre distance and allowing 360° orientation
- Maintenance by releasing the 2 closing screws, removing the end cap and extracting the gear tray

Characteristics

- Warranty : 8 years 24/7 use at max temp
- Operating temperature: -20°C +35°C
- Protection: IP66/IP68/IP69K
- Resistance to IK shocks: IK07
- Class I
- Supply voltage: 220-240V 50/60Hz
- Power consumption: 70 W
- Luminous efficacy: 132 lm/W
- Power factor > 0,95
- THD: 13,3 %
- Inrush current - Ipeak: 21 A
- Photobiological hazard: Group 0
- Peak duration - Twidth: 316 µs
- Number of luminaires on automat type B16: 19 pcs
- T°C with incandescent wires: non-flammable
- Vibration resistance: Meets the severe application requirements of the standard EN 60598-1 (tested according to CEI 60068-2-6)
- Weight: 10,5 kg
- Designed and made in France

© Sammode – 24 sept. 2024 - Technical specifications subject to change