# AIRMOD





800


1200

1600

Description AIRMOD MONO suspension light with surface-mounted power supply box (Stefan Diez design).BRONZE finishing.Equipped with an interchangeable GLASS shade SMOKED.Low-voltage head, diameter 100, can swivel through 360° thanks to a nickel-plated copper double hoop.Bronze anodised aluminium fin passive heat sink.Interchangeable tubular shade in smoked tempered glass

### Light specifications and controlling

- CoB LED Module 900 Im (without endcap), IRC>90, 2700 K, 3 SDCM
- Interchangeable optics unit composed of a mixing chamber and a sandblasted glass lens with controlled lateral glare
- Constant Current Driver (non-dimmable)



cd

## 96 Ø 113 ଞ <3 m 160 Ø 100

#### Installation and maintenance


- Dimensions : Head : Ø100x160 mm, Box : Ø113x60 mm
- Box in anodised aluminium containing a 220-240 V 50/60 Hz power supply and a 3 x 2.5 mm<sup>2</sup> terminal block
- For surface mounting via 2 x M3 screws with centre distance 96 mm (not supplied).
- Suspension wires adjustable in height, up to 3 m.



### **Characteristics**

- Warranty: 5 years
- 50 000 h L80/B10 at 25°C
- Operating temperature: -5 °C to +35 °C
- Protection : IP20
- Electrical class: Class I

- Power consumption: 13 W
- Photobiological hazard: Group 1
- Fire resistance: 850 °C
- Weight: 1,25 kg
- · Designed and made in France and Germany



1 head : 1180 lm