
GUDE 100 360°






Description

- Tubular wall light GUDE 100 360° (design: Dominique Perrault & Gaëlle Lauriot- • Coal-coloured (RAL 7021) painted aluminium Prévost)
- For omnidirectional lighting with rectangular perforation grid
- Grid with COAL finishing
- Housing: Co-extruded polycarbonate/PMMA
 Gaskets: Gaskets moulded in EPDM for inside/outside use
- End caps & fixing straps: Stainless steel 304L
- grid inserted between housing and an internal film in opalised white polycarbonate
- · Stainless steel mounting plate attached to the alimentation end cap



Light specifications and controlling

- 1 E27 11W max lamp, not included
- non dimmable




Ø100 mm

Installation and maintenance

- Diameter: 100 mm
- Total length: 355 mm
- Cable entry with nickel-coated brass cable gland for cable Ø 5 14 mm
- Connection to 3x2.5mm² automatic terminal block
- 2 reinforced stainless Steel fixing straps (with variable centre distance) and allowing 360° orientation
- · Installation in vertical position, cable gland positioned downwards
- · Maintenance by releasing the closing screw and extracting the diffuser







Characteristics

- Operating temperature: -20 °C to +35 °C
- Protection: IP66/IP68/IP69K
- Resistance to IK shocks: IK10
- Electrical class: Class I

- Power supply: 220-240 V 50/60 Hz
- T°C with incandescent wires: 650°C
- Weight: 1,5 kg
- Designed and made in France