VENDOME MINI

80310005 **VENDOME 100 2L S S 500 CL1** Tubular wall light






- Tubular wall light VENDOME 100 2L (design: Normal Studio)
- Honeycomb perforation grid
- Grid with SILVER finishing
- Housing: UV-resistant co-extruded polycarbonate/PMMA for inside/outside use • Gaskets: Gaskets moulded in EPDM
- End caps & fixing straps: Stainless steel 304L
- Anodised aluminium reflector: SILVER
- Silver anodised aluminium grid inserted inside the housing
- Stainless steel gear tray with 2 porcelaine sockets E14



η = 42% cd/klm C0 - C180 - - - C90 - C270

Light specifications and controlling

- 2 E14 11W max lamps, not included
- non dimmable



Installation and maintenance

- Diameter: 100 mm
- Total length: 519 mm
- Connection to 3x2.5mm² automatic terminal block
- 2 reinforced stainless Steel fixing straps (with variable centre distance) and allowing 360° orientation
- Installation in vertical position, cable gland positioned downwards













Characteristics

- Warranty: 5 years
- Operating temperature: -20 °C to +35 °C
- Protection: IP66/IP68/IP69K
- Resistance to IK shocks: IK10
- Electrical class: Class I

- Power supply: 220-240V 50/60Hz
- T°C with incandescent wires: 650°C
- Weight: 1,6 kg
- · Designed and made in France