MONCEAU MINI

80310007 MONCEAU 100 2L B B 500 CL1 Tubular wall light






- Tubular wall light MONCEAU 100 2L (design: Anodised aluminium reflector: BRASS Normal Studio)
- · Chevron perforation grid
- Grid with BRASS finishing
- Housing: UV-resistant co-extruded polycarbonate/PMMA for inside/outside use
- End caps & fixing straps: Stainless steel 304L
- Brass anodised aluminium grid inserted inside the housing
- Stainless steel gear tray with 2 porcelaine sockets E14
- Gaskets: Gaskets moulded in EPDM



$\eta = 63\%$ cd/klm C0 - C180 - - - C90 - C270

Light specifications and controlling

- 2 E14 11W max lamps, not included
- non dimmable



Installation and maintenance

- Diameter: 100 mm
- Total length: 519 mm
- Connection to 3x2.5mm² automatic terminal block
- 2 reinforced stainless Steel fixing straps (with variable centre distance) and allowing 360° orientation
- Installation in vertical position, cable gland positioned downwards













Characteristics

• Warranty: 5 years

• Operating temperature: -20 °C to +35 °C

• Protection: IP66/IP68/IP69K

• Resistance to IK shocks: IK10

• Electrical class: Class I

• Power supply: 220-240V 50/60Hz

• T°C with incandescent wires: 650°C

• Weight: 1,6 kg

· Designed and made in France