
# **MONCEAU** MINI






## Description

- Normal Studio)
- Chevron perforation grid
- Color: COAL (RAL 7021)
- · Grid with COAL finishing
- Housing: UV-resistant co-extruded polycarbonate/PMMA for inside/outside use
- Tubular wall light MONCEAU 100 2L (design: End caps & fixing straps: stainless steel 304L painted COAL (RAL 7021)
  - Anodised aluminium reflector : PETROL
  - Coal-coloured (RAL 7021) painted aluminium grid inserted inside the housing
  - Stainless steel gear tray with 2 porcelaine sockets E14
  - Gaskets: Gaskets moulded in EPDM



#### Light specifications and controlling

- 2 E14 11W max lamps, not included
- non dimmable



5

IK10

CE

# Installation and maintenance

- Diameter: 100 mm
- Total length: 519 mm
- Connection to 3x2.5mm<sup>2</sup> automatic terminal block
- 2 reinforced stainless Steel fixing straps (with variable centre distance) and allowing 360° orientation
- Installation in vertical position, cable gland positioned downwards

## **Characteristics**

- Warranty: 5 years
- Operating temperature: -20 °C to +35 °C
- Protection: IP66/IP68/IP69K
- Resistance to IK shocks: IK10
- Electrical class: Class I

- Power supply: 220-240V 50/60Hz
- T°C with incandescent wires: 650°C
- Weight: 1,6 kg
- Designed and made in France