AIRMOD






60

8

Ø 100

ß



Description

AIRMOD DUO double suspension light with surface-mounted power supply box (Stefan Diez design).SILVER finishing.Equipped with an interchangeable GLASS shade FROSTED.Two lowvoltage heads, diameter 100, can be oriented through 360° thanks to a nickel-plated copper double hoop.Silver anodised aluminium fin passive heat sink.Interchangeable tubular shade in frosted tempered glass

Light specifications and controlling

- CoB LED Module 900 Im (without endcap), IRC>90, 2700 K, 3 SDCM
- Interchangeable optics unit composed of a mixing chamber and a sandblasted glass lens with controlled lateral glare
- Constant Current Driver (non-dimmable)

Installation and maintenance

- Dimensions : Head : Ø100x160 mm, Box : 660x50x60 mm
- Box in anodised aluminium containing a 220-240 V 50/60 Hz power supply and a 3 x 2.5 mm² terminal block
- For surface mounting via 2 x M3 screws with centre distance 450 mm (not supplied).
- Suspension wires adjustable in height, up to 3 m.



450

660

- <3 m -

Characteristics

- Warranty: 5 years
- 50 000 h L80/B10 at 25°C
- Operating temperature: -5 °C to +35 °C
- Protection : IP20
- Electrical class: Class I
- Power consumption: 26 W
- Photobiological hazard: Group 1
- Fire resistance: 850 °C
- Weight: 2,29 kg
- · Designed and made in France and Germany

