




Description

AIRMOD RCSD suspension light with recessed equipment housing (Stefan Diez design).BLACK finishing.Equipped with an interchangeable perforated collimator GRID, BLACK finishing.Low-voltage head, diameter 100, can swivel through 360° thanks to a nickel-plated copper double hoop.Black anodised aluminium fin passive heat sink.Interchangeable perforated tubular collimator in black anodised aluminium



cd
— C0 - C180 - - - C90 - C270


1 head : 900 lm

Light specifications and controlling

- CoB LED Module 900 lm (without endcap), IRC>90, 2700 K, 3 SDCM
- Interchangeable optics unit composed of a mixing chamber and a Wide Beam 50° glass lens
- Constant Current Driver (non-dimmable)

Installation and maintenance

- Dimensions : Head : Ø100x160 mm
- Prewired driver, fitted with a male-female Wieland coupling. 220-240 V 50/60Hz power supply
- Fixing device on hollow partition with two fastening screws (included), covered with an anodized aluminium covering plate (diameter of the installation hole : 83 mm, wall thickness : 30 mm max, empty plenum height : 100 mm mini)
- Suspension wires adjustable in height, up to 3 m.



Characteristics

- Warranty : 5 years
- 50 000 h L80/B10 at 25°C
- Operating temperature: -5 °C to +35 °C
- Protection : IP20
- Electrical class: Class I
- Power consumption: 13 W
- Photobiological hazard: Group 1
- Fire resistance: 850 °C
- Weight: 1,03 kg
- Designed and made in France and Germany