AIRMOD





AIRMOD RCSD suspension light with recessed equipment housing (Stefan Diez design).BLACK finishing.Equipped with an interchangeable GLASS shade FROSTED.Low-voltage head, diameter 100, can swivel through 360° thanks to a nickel-plated copper double hoop.Black anodised aluminium fin passive heat sink.Interchangeable tubular shade in frosted tempered glass

Description

900 1 head : 800 lm cd - C0 - C180 - - - C90 - C270

Ø**83** Ř с З Ш 160

CRI 90

IRC 90

Installation and maintenance

Light specifications and controlling

Constant Current Driver (non-dimmable)

controlled lateral glare

• CoB LED Module 900 Im (without endcap), IRC>90, 2700 K, 3 SDCM

- Dimensions : Head : Ø100x160 mm
- Prewired driver, fitted with a male-female Wieland coupling. 220-240 V 50/60Hz power supply

• Interchangeable optics unit composed of a mixing chamber and a sandblasted glass lens with

- Fixing device on hollow partition with two fastening screws (included), covered with an anodized aluminium covering plate (diameter of the installation hole : 83 mm, wall thickness : 30 mm max, empty plenum height : 100 mm mini)
- Suspension wires adjustable in height, up to 3 m.

Characteristics

- Warranty: 5 years
- 50 000 h L80/B10 at 25°C
- Operating temperature: -5 °C to +35 °C
- Protection : IP20
- Electrical class: Class I
- Power consumption: 13 W
- Photobiological hazard: Group 1
- Fire resistance: 850 °C
- Weight: 1,14 kg
- · Designed and made in France and Germany

LED