# **GUDE 100** 360°


80300010 GUDE 100 360° S 350 CL1 Tubular wall light






### Description

- Tubular wall light GUDE 100 360° (design: Dominique Perrault & Gaëlle Lauriot- • Stainless steel grid inserted between housing Prévost)
- For omnidirectional lighting with rectangular perforation grid
- Grid with SILVER finishing
- Housing: Co-extruded polycarbonate/PMMA Gaskets: Gaskets moulded in EPDM for inside/outside use
- End caps & fixing straps: Stainless steel 304L
- and an internal film in opalised white polycarbonate
- Stainless steel mounting plate attached to the alimentation end cap



### Light specifications and controlling

- 1 E27 11W max lamp, not included
- non dimmable



## Installation and maintenance

- Diameter: 100 mm
- Total length: 355 mm
- Cable entry with nickel-coated brass cable gland for cable Ø 5 14 mm
- Connection to 3x2.5mm² automatic terminal block
- 2 reinforced stainless Steel fixing straps (with variable centre distance) and allowing 360°
- Installation in vertical position, cable gland positioned downwards
- · Maintenance by releasing the closing screw and extracting the diffuser











#### **Characteristics**

• Warranty: 5 years

• Operating temperature: -20 °C to +35 °C

• Protection: IP66/IP68/IP69K

• Resistance to IK shocks: IK10

• Electrical class: Class I

• Power supply: 220-240 V 50/60 Hz

• T°C with incandescent wires: 650°C

• Weight: 1,5 kg

· Designed and made in France