


Description

- Suspended tubular light KYHN 133 360° (design: Dominique Perrault & Gaëlle Lauriot-Prévost)
- For omnidirectional lighting with rectangular perforation grid
- Grid with SILVER finishing
- Housing: UV-resistant co-extruded polycarbonate/PMMA for inside/outside use
- End caps & fixing straps: Stainless steel 304L
- Stainless steel grid inserted between housing and an internal film in opalised white polycarbonate
- Gear tray: Internal white lacquered steel gear tray
- Passive heat sink in aluminium
- Gaskets: Gaskets moulded in EPDM



Light specifications and controlling

- High-efficiency removable LED modules (IRC>80, 3 SDCM)
- Luminous flux: 2000 lm
- Colour temperature: 3000 K
- Specific satin-finish primary diffuser optic
- Constant Current Driver (non-dimmable)

Installation and maintenance

- Diameter: 133 mm
- Total length: 1595 mm
- Cable entry with nickel-coated brass cable gland for cable Ø 5 - 14 mm
- Connection to a 3 x 2.5 mm² disconnectable terminal block
- 2 reinforced stainless Steel fixing straps (with variable centre distance) and allowing 360° orientation
- Provided with 2 suspension kits including: A ceiling-mounting system, 3m of Ø1.2mm steel wire and self-locking adjustable fixing system for bolt fitted fixing strap
- Quick opening and closing with just one screw
- Patented SLIDE maintenance system
- Removable LED modules and driver

Characteristics

- Warranty : 5 years
- 50 000 h L80/B10 at 25°C
- Operating temperature: -20°C to +30°C
- Protection: IP66/IP68/IP69K
- Resistance to IK shocks: IK10
- Electrical class: Class II
- Supply voltage: 220-240V 0/50/60Hz
- Power consumption: 52 W
- Inrush current - I_{peak}: 57,7 A
- Photobiological hazard: Group 0
- Peak duration - T_{width}: 217 µs
- T°C with incandescent wires: 650°C
- Number of luminaires on automat type B16: 10 pcs
- Weight: 7,2 kg
- Designed and made in France

