




Description

- BOYLE 133 tubular light fitting for explosive environments, Zone 2 (Gaz) or Zones 21&22 (Dusts) classified
- End-caps ½ ring press-formed
- Optical diffuser
- Ø135 mm borosilicate-glass diffuser
- Single-piece housing with high mechanical and reinforced seal, silicone-free
- White powder-coated mounting plate
- Passive heat sink in aluminium
- Moulded EPDM gaskets




Light specifications and controlling

- High efficiency replaceable LED modules (IRC>80, 70 000 hours L80/B10@Tmax)
- Luminous flux: 7400 lm
- Colour temperature: 4000K
- Light mixing chamber
- Resistant LED driver 'Industry', non-dimmable
- Compatible with neutral TN, TT and IT arrangements with no limitations


Installation and maintenance

- Diameter: 133 mm
- Total length: 1287 mm
- 2 ATEX polyamide cable gland, of which 1 closed, for loop-in loop out wiring (capacity: Ø8 à 13 mm). max amperage 10A
- Connection to 5x2,5mm² detachable double deck terminal block, compatible with three-phase grid
- 2 reinforced fixing straps in stainless steel with variable centre distance and allowing 360° orientation
- Off-load opening in an explosive environment
- Maintenance by releasing the 2 closing screws, removing the end cap and extracting the gear tray



Characteristics

- Warranty : 8 years 24/7 use at max temp
- Operating temperature: -20°C +50°C
- Protection: IP66/IP68/IP69K
- Resistance to IK shocks: IK07
- Class I
- Supply voltage: 220-240V 0/50/60Hz
- Power consumption: 56 W
- Luminous efficacy: 132 lm/W
- Power factor > 0,95
- THD: 6,8 %
- Inrush current - Ipeak: 5 A
- Peak duration - Twidth: 1000 µs
- T°C with incandescent wires: non-flammable
- Number of luminaires on automat type B16: 32 pcs
- Vibration resistance: Meets the severe application requirements of the standard EN 60598-1 (tested according to CEI 60068-2-6)
- Weight: 9,4 kg
- ATEX approved (Licenses INERIS 15ATEX3002X/INERIS 15ATEX0005X)
- II 3G Ex ec IIC T4 Gc (Zone 2) - II 2D Ex tb IIIC T70°C Db IP66/IP68 (Zones 21&22)
- IECEx approved (License IECEx INE 15.0014X)



- Designed and made in France