


Description

- MUSSET tubular light fitting
- Color: MARSALA (RAL 3011)
- End caps & fixing straps: stainless steel 304L painted MARSALA (RAL 3011)
- Flux-breaker grids in stainless steel, painted MARSALA (RAL3011)
- Anodised aluminium reflector : SILVER
- Ø100 mm borosilicate-glass diffuser
- Stainless steel gear tray with 2 porcelaine sockets E14
- Moulded EPDM gaskets
- High temperature internal wiring with silicone isolation braided with glass fibre



Light specifications and controlling

- 2 E14 11W max lamps, not included



Installation and maintenance

- Total length: 519 mm
- Connection to 3x2,5mm² detachable terminal block
- 2 reinforced stainless Steel fixing straps (with variable centre distance) and allowing 360° orientation
- Installation in vertical position, cable gland positioned downwards
- Maintenance by releasing the 2 closing screws, removing the end cap and extracting the gear tray



Characteristics

- Warranty : 5 years
- Operating temperature: -20°C to +30°C
- Protection: IP66/IP68/IP69K
- Resistance to IK shocks: IK07
- Electrical class: Class I
- Power supply: 220-240 V 50/60 Hz
- T°C with incandescent wires: non-flammable
- Weight: 2,7 kg