
ALDER

19905214 ALD133 1300 6200-840 POME 213 BRS










Description

- ALDER tubular light fitting for explosive environments, Zone 1
- End-caps ½ ring press-formed
- Diffuser Ø133mm in polycarbonate, protected from UV, solvents, hydrocarbons and cleaning agents by a coextrusion of methacrylate
- · White powder-coated mounting plate guided and lockable
- · Passive heat sink in aluminium
- Moulded EPDM gaskets



- High efficiency replaceable LED modules (IRC>80, 70 000 hours L80/B50@Tmax)
- · Luminous flux: 6200 lm
- Colour temperature: 4000K
- Specific satin-finish primary diffuser optic
- · Non-dimmable LED driver
- Compatible with neutral TN, TT and IT arrangements with no limitations







Installation and maintenance

- Diameter: 133 mm
- Total length: 1295 mm
- 2 ATEX polyamide cable gland,of which 1 closed, for loop-in loop out wiring (capacity: Ø8 à 13 mm). max amperage 10A
- Connection to 5x2,5mm² detachable double deck terminal block, compatible with three-phase grid
- 2 reinforced fixing straps in stainless steel with variable centre distance and allowing 360° orientation
- · Off-load opening in an explosive environment
- Maintenance by removing the end cap and sliding the guided gear plate

















Characteristics

- Warranty: 8 years 24/7 use at max temp
- Operating temperature: -20 °C to +35 °C
- Protection: IP66/IP68/IP69K
- Resistance to IK shocks: IK10
- Class I
- Supply voltage: 220-240V 50/60Hz
- Power consumption: 52 W
- Luminous efficacy: 119 lm/W
- Power factor > 0,95
- THD: 6 %
- Inrush current Ipeak: 22 A

- Peak duration Twidth: 200 μs
- T°C with incandescent wires: 650°C
- Number of luminaires on automat type B16: 24 pcs
- · Vibration resistance: Meets the severe application requirements of the standard EN 60598-1 (tested according to CEI 60068-2-6)
- Weight: 7,8 kg
- ATEX approved (License INERIS 19ATEX0002X)
- II 2G Ex eb mb IIC T6 Gb (Zones 1&2) II 2D Ex tb IIIC T80°C Db IP66 (Zones 21&22)
- Temperature class: T6 (Gaz)
- IECEx approved (License IECEx INE 19.0004X)
- · Designed and made in France