SABATIER

19910806 SAB133 700 3100-840 PY 213 BRS Tubular light fitting for explosive environments






Description

- SABATIER tubular light fitting for explosive environments, Zone 1
- End-caps ½ ring press-formed
- Ø135 mm borosilicate-glass diffuser
- White powder-coated mounting plate
- Passive heat sink in aluminium
- · Moulded EPDM gaskets

Light specifications and controlling

- High efficiency replaceable LED modules (IRC>80, 50 000 hours L80/B10@Tmax)
- · Luminous flux: 3100 lm
- Colour temperature: 4000K
- Specific satin-finish primary diffuser optic
- Non-dimmable LED driver
- Compatible with neutral TN, TT and IT arrangements with no limitations



677 Entraxe variable Ø133

Installation and maintenance

- Diameter: 135 mm
- Total length: 677 mm
- 2 ATEX polyamide cable gland,of which 1 closed, for loop-in loop out wiring (capacity: Ø8 à 13 mm). max amperage 10A
- Connection to 5x2,5mm² detachable double deck terminal block, compatible with three-phase
- Stud welded to the input end cap for any bonding connections
- 2 reinforced fixing straps in stainless steel with variable centre distance and allowing 360° orientation
- · Off-load opening in an explosive environment
- · Maintenance by releasing the 2 closing screws, removing the end cap and extracting the gear tray


















Characteristics

- Warranty: 5 years 24/7 use at max temp
- Operating temperature: -20°C +50°C
- Protection: IP66/IP68/IP69K
- Resistance to IK shocks: IK07
- Class I
- Supply voltage: 220-240V 50/60Hz
- Power consumption: 28 W
- · Luminous efficacy: 111 lm/W
- Power factor > 0,9
- THD: 9 %
- Inrush current Ipeak: 22 A

- Peak duration Twidth: 200 μs
- T°C with incandescent wires: non-flammable
- Vibration resistance: Meets the severe application requirements of the standard EN 60598-1 (tested according to CEI 60068-2-6)
- Number of luminaires on automat type B16: 24 pcs
- Weight: 7,7 kg
- ATEX approved (License INERIS 19ATEX0002X)
- II 2G Ex eb mb IIC T5 Gb (Zones 1&2) II 2D Ex tb IIIC T80°C Db IP66 (Zones 21&22)
- Temperature class: T5 (Gaz)
- IECEx approved (License IECEx INE 19.0004X)



Designed and made in France	