ELGAR


14336138

ELGAR 70 PU P 450 275-827 BPI CRP MR P12











- Internal anodized finishing aluminum gear unit
 Internal grey lacquered steel gear tray RAL cover: PETROL
- Housing: UV-resistant co-extruded polycarbonate/PMMA for inside/outside use
- End caps & fixing straps: Stainless steel 316L
- · Longitudinal louvre in aluminum petrol color with inclined lamina
- and screws in A4 stainless steel
- 9006
- · Gaskets: Gaskets moulded in EPDM
- · Integrated push-button on the end cap



Light specifications and controlling

- High-efficiency removable LED modules (IRC>80, 3 SDCM)
- Luminous flux: 275 lm
- Colour temperature: 2700 K
- · Specific satin-finish primary diffuser optic
- · Reversible longitudinal louvre
- · Constant Current Driver for dimming by integrated push-button



Installation and maintenance

- Diameter: 70 mm
- Total length: 430 mm
- · Cable entry with nickel-coated brass cable gland for cable Ø 8 - 12 mm
- Supplied with a 2 x 0.75 mm² black 2 m cable with a European plug for indoor use
- Connection to 2x2.5mm² automatic terminal block
- 2 reinforced fixing straps in stainless steel with variable centre distance and allowing 360° orientation
- Opening and closing by tightening the nut on the cable gland
- Installation vertical: position cable gland positioned downwards
- · Maintenance by removing the end cap and sliding the guided gear plate
- · Easily removable LED modules and driver















Characteristics

- Warranty: 5 years
- 50 000 h L80/B10 at 25°C
- Operating temperature: -20 °C to +35 °C
- Imperviousness: IP65, for indoor use
- · Resistance to IK shocks: IK10
- · Electrical class: Class II
- Power supply: 220-240 V 50/60 Hz
- Power consumption: 8 W
- · Luminous efficacy: 34 lm/W

- Power factor > 0,9
- THD: 18 %
- Photobiological hazard: Group 0
- Inrush current Ipeak: 5 A
- Fire resistance: 650 °C
- Number of luminaires on automat type B16: 130 pcs
- Weight: 1,1 kg
- · Designed and made in France